



tradition • innovation • quality

a.b.e.® Construction Chemicals

abe® membrane

DO-IT-YOURSELF

HIGH STRENGTH POLYESTER REINFORCED MEMBRANE



Parapet walls, roof laps, flashings

WATERPROOFING

DESCRIPTION

abe® membrane is a high strength polyester stitch bond non-woven reinforcing membrane for use with **a.b.e.®** waterproofing systems.

USES

Suitable for use with **a.b.e.®** waterproofing and flashing systems.

ADVANTAGES

- High strength.
- Reinforce waterproofing systems.
- Will not shrink or perish.
- Bridges cracks and gaps.

SURFACE PREPARATION

Surfaces must be clean and free from dust and grease. Must be used in accordance with the waterproofing or flashing specification of the product.

COVERAGE

As required.

APPLICATION

Follow the waterproofing or flashing specification of the product it gets used with.

COLOUR



PROTECTION ON COMPLETION

abe® membrane will not perish, but need to be overcoated as specified by the waterproofing system.

PACKAGING

abe® membrane is supplied in the following sizes:

1 m x 1 m	200 mm x 12.5 m
10 m x 1 m	200 mm x 20 m
100 mm x 10 m	250 mm x 10 m
100 mm x 20 m	250 mm x 20 m
200 mm x 2.5 m	300 mm x 20 m
200 mm x 10 m	500 mm x 10 m

PHYSICAL PROPERTIES

Weight	80 – 100 g/m ²
--------	---------------------------

HANDLING AND STORAGE

Shelf-life of 24 months if kept in a dry cool place in the original packaging.

DATE UPDATED: 27/05/2021

a.b.e.® is an ISO 9001:2015 registered company
Registration Number: 1982/005383/07
101 Main Reef Road, Boksburg North, 1459
PO Box 5100, Boksburg North, 1461

a.b.e.® Construction Chemicals (Pty) Ltd
is a CHRYSO Group Company

