



# a.b.e.<sup>®</sup> Construction Chemicals super laykold tape

## A PEEL AND STICK WATERPROOFING TAPE

### DESCRIPTION

**super laykold tape** is a bitumen aluminium self-adhesive waterproofing tape.

### USES

Seals and repairs leaky, galvanised roof sheeting, holes and overlaps, valley gutters, downpipes, roof screws, pipe vents, ridging and capping.

### ADVANTAGES

- Peel and stick
- Easy to use
- Self adhesive

### SURFACE PREPARATION

Surface to be covered must be clean, sound, dry and free of any grease, oils and loose materials. Allow material to warm in sun before application.

### BONDING/PRIMING

Prime surfaces with **abe<sup>®</sup> tape primer**.

**abe<sup>®</sup> tape primer** must be applied to a dry substrate. Allow 4 hours for drying before applying **super laykold tape**.

### MIXING

**super laykold tape** is supplied in rolls ready for use.

### COVERAGE

**super laykold tape** is supplied in roll form in various sizes. Use size as required.

### APPLICATION

Cut to size before removing plastic rapping and apply **super laykold tape** to the required area.

**Sealing:** overlaps needs to be a minimum of 50 mm as flashing between a wall and a corrugated roof, gaps must be filled with **bitu.<sup>®</sup> seal plastic**, or cement.

### TYPICAL PHYSICAL PROPERTIES

Resistance to weathering	Excellent
Surface finish	Aluminium
Thickness of aluminium	50 µm
Thickness of adhesive	1 750 µm
Total thickness	1 800 µm
Adhesion to metal, plastics, primed concrete and self	2,0 N/mm min

### CLEANING

Tools, brushes and mixing equipment should be cleaned immediately after use and before material has set with **abe<sup>®</sup> super brush cleaner** followed by washing with soap and water.

### PROTECTION ON COMPLETION

**super laykold tape** is to be left with the aluminium protective layer as is after application.

### TEMPERATURE AND RELATIVE HUMIDITY

Application temperature range:

5°C to 40°C

**super laykold tape** must not be applied in freezing, wet or foggy conditions.

### MODEL SPECIFICATION

Self-adhesive sealing tape for repairs to galvanised and fibre cement roofs. Primer: **abe<sup>®</sup> tape primer** for porous surfaces.

The waterproofing tape will be **super laykold** waterproofing tape, a self-adhesive, bituminous compound with a laminated aluminium reflective facing applied in accordance with the recommendations of **a.b.e.<sup>®</sup> Construction Chemicals**, including **abe<sup>®</sup> tape primer**.

## PACKAGING

**super laykold tape** is supplied in rolls of varying sizes:

2,5 m x 50 mm  
2,5 m x 75 mm  
2,5 m x 100 mm  
2,5 m x 150 mm  
5 m x 100 mm  
5 m x 150 mm  
10 m x 75 mm  
10 m x 100 mm

## HANDLING & STORAGE

This product has a shelf life of 12 months if kept in a dry cool place in the original packaging. In more extreme conditions this period might be shortened

## HEALTH & SAFETY

The use of gloves and eye protection is advised. Always ventilate the working area well during application and drying. Avoid flames in vicinity. If material is splashed into the eye wash with plenty of clean water and seek medical attention.

Cured **super laykold tape** is inert and harmless.

## IMPORTANT NOTE

This data sheet is issued as a guide to the use of the

product(s) concerned. Whilst **a.b.e.® Construction Chemicals** endeavours to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot - because **a.b.e.®** has no direct or continuous control over where and how **a.b.e.®** products are applied - accept any liability either directly or indirectly arising from the use of **a.b.e.®** products, whether or not in accordance with any advice, specification, recommendation, or information given by the company.

## FURTHER INFORMATION

Where other products are to be used in conjunction with this material, the relevant technical data sheets should be consulted to determine total requirements.

**a.b.e.® Construction Chemicals** has a wealth of technical and practical experience built up over years in the company's pursuit of excellence in building and construction technology.



a.b.e.® is an ISO 9001:2008 registered company  
PO Box 5100, Boksburg North, 1461, South Africa  
Website: [www.abe.co.za](http://www.abe.co.za) | Tel: +27(0) 11 306 9000  
Durban | Johannesburg | Cape Town | Port Elizabeth | East London | Bloemfontein | George

a.b.e.® is a Chryso Group Company

**CHRYSO**  
CHEMICAL SOLUTIONS FOR THE  
CONSTRUCTION MATERIALS INDUSTRY  
DATE UPDATED: 17/11/14