



DIY Waterproofing and Damp-proofing solutions.

Wonder-Fill Multi-purposefiller

Discussion

WONDER-FILL is a ready mixed, easy to use multipurpose, interior and exterior, which dries to a tough semi flexible, sand able and paintable surface with 101 uses around the home. WONDER-FILL is suitable for repairing and filling gaps, cracks, holes and other blemishes on walls, floors, skirtings, ceilings, hollow core doors, door and window frames. Wonder-fill is an acrylic based filler which has excellent adhesive properties to almost all building substrates (concrete, plaster, brick, paint, timber, masonite, plaster board and metal) Because of its adhesive properties WONDER-FILL can successfully be used as a tile adhesive for small repair work as well as replacing damaged window putty. WONDER-FILL is available in 25L, 5L, 1L and 300gram containers.

Physical Properties

Colour:	Off white
Application:	Trowel, scraper or putty knife.
Coverage:	1m ² /L (1mm film thickness)
Specific Gravity:	+/- 1.85
Viscosity:	Thick paste like consistency
Drying Time:	Depends on film thickness
Cleaning:	Water

TECHNICAL DATA SHEET



DIY Waterproofing and Damp-proofing solutions.

Surface preparation

All forms of surface contamination must be removed to ensure a smooth surface, free of moisture and any loose material, or any other barrier to adhesion.

Old dusty porous surfaces such as concrete, plaster, brick etc. can be dampened with a small amount of water before application, to ensure a stronger bond.

Technical assistance and applicator training are freely available to all approved users.

Application

Stir WONDER-FILL before use

WONDER-FILL can be diluted with water but it will make the finished product more susceptible to hair line cracking.

Apply WONDER-FILL with a trowel, scraper or putty knife.

Apply in layers not more than 10mm thick, allowing each layer to dry before the next application.

Finishing layers should be smoothed off while wet.

If applied too thickly, slight hair line cracks may appear during drying; a thin final application of WONDER-FILL should be applied.

After drying the surface may be sanded, dusted off and over-coated with chosen paint.

For easier sanding of WONDER-FILL use a wet sponge sanding block for a quick and easy smooth finish.

Technical assistance and applicator training are freely available to all approved users.

TECHNICAL DATA SHEET