



RAW LINSEED OIL

DESCRIPTION:

Powafix Raw Linseed Oil is an amber coloured slow drying natural oil for exterior timber.

RECOMMENDED USES:

- Timber windows and frames.
- Coating over window putty.
- Timber palisades and fences.
- Cricket bats.

FEATURES & BENEFITS:

- Amber coloured slow drying natural oil for exterior timber.
- Seals and protects.
- Drying time 7-10 days.

DIRECTIONS FOR USE:

- Remove excess loose or flaking material.
- Timber should not be excessively wet.
- Timber should be cleaned with Powafix Liquid Sugar Soap prior to painting.
- Apply Powafix Raw Linseed Oil liberally with a block brush or similar coarse bristle brush.
- New timber not previously treated should be coated with a minimum of 2 coats. Drying time 7 – 10 days.
- A maintenance coat should be applied every 12 – 18 months.
- Clean equipment with Powafix Mineral Turpentine.

USAGE AND STORAGE PRECAUTIONS:

- Ensure cap is tightly sealed and packaging is secure and upright at all times.
- Store product in cool, well-ventilated area.
- Secure product when transporting to prevent accidental spillage.
- Keep product away from heat, flames, sunlight, static or electricity sparks.
- In the event of a fire, use Carbon Dioxide Foam or Chemical Powder, **NOT WATER**.
- Dispose of container-do not use for any other purpose.
- Do not dispose product into common waste system.
- Contact 0860 254 620 for product disposal enquiries.



More than just a product.

TIMBER TREATMENT PRODUCTS TECHNICAL DATA SHEET



SAFETY INSTRUCTIONS

READ INSTRUCTIONS BEFORE USE



WARNING! Causes eye irritation. Use protective glasses. If contact with eyes occurs, flush open eyes with plenty of water and seek immediate medical attention.



WARNING! Causes mild skin irritation. Wear protective gloves. Avoid contact with skin. If contact with skin occurs, wash with soapy water. Do not eat, drink or smoke when using product. Take off contaminated clothing and wash before re-use.



Store in a secure location, out of reach of children and animals. If swallowed do not induce vomiting and seek immediate medical attention.

Poison Info. Line: 021 689 5227 / 0861 555 777



GALLERY:

		
750ml Bottle 12 per case LIN750MLRS 6009600991293	5L Bottle 4 per case LIN5LR 6009600991309	25L Polycan Single unit LIN25LR 6009600991316

*200L image available on request

COLOUR:

- Clear amber.

ASSOCIATED PRODUCTS:

- Powafix Liquid Sugar Soap
- Powafix Mineral Turpentine
- Powafix Powastrip Paint Stripper

SPECIFIC DATA:

APPEARANCE:	CLEAR AMBER LIQUID.
SG @23°C:	0.93
APPLICATION TEMP:	8°C → 35°C
OPEN TIME:	N/A
MAXIMUM APPLICATION:	N/A
SHELF LIFE:	MINIMUM 12 MONTHS WHEN STORED TO MANUFACTURERS RECOMMENDATIONS.
DRYING TIME:	7 – 10 DAYS.

CODE & ISSUE DATE:

LINR JAN 2017

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.