



TECHNICAL DATA SHEET: CLEANERS & REMOVERS



POWASTRIP®

1. **DESCRIPTION** : Fast Acting Paint remover

2. **FEATURES AND BENEFITS:**

- Removes multiple layers of enamels, varnishes and 2k coatings.
- Suitable for use on metal, timber, and concrete surfaces
- Gel formula is suitable for vertical surfaces.



- UN1593

3. **USAGE PRECAUTIONS:**



Read all instructions before use. Corrosive product, handle with caution and follow all safety instructions. Product contains Methylene Chloride. Shake well before use. Contents may be under pressure, open cap with caution to prevent any splashing. Do not apply to hot surfaces. Do not dilute or mix with other chemicals. Test substrate suitability before use. Not suitable for use on plastics and fibre glass surfaces. Contact our product support line on 072 396 4980 for assistance prior to applying.

4. **DIRECTIONS FOR USE:**

4.1. **SURFACE PREPARATION :**

- Remove all loose and flaking material. Use a Powafix Protection Sheet to protect surfaces that are not being treated.




TECHNICAL DATA SHEET: CLEANERS & REMOVERS



4.2. APPLICATION INSTRUCTIONS:

- Apply a liberal coat of Powastrip to the surface. Paint surface will bubble after 5 – 10 minutes. Once the coating softens and lifts from the surface use a scraper to remove. Use a wire brush for difficult to reach areas. Additional applications may be needed for multiple layers of paint.
- Use a wire brush or scraper to remove any remaining Powastrip and clean treated surfaces with Powafix Sugar Soap*.

5. STORAGE PRECAUTIONS :

 Ensure lid is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store locked up in a cool place out of reach of children. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact 0860 254 620 for disposal information. Discard product 18 months after batch date.

6. SAFETY INSTRUCTIONS:



– corrosive, organ toxicity

DANGER Harmful if swallowed. Causes skin irritation. Causes serious eye damage. Suspected of causing cancer. Toxic to aquatic life.



Read all instructions before use. Use product within well ventilated areas. Keep out of reach of children. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash before reuse. If medical advice is needed, have product packaging at hand. Use personal protective equipment as required. Wear protective gloves. Wear eye protection. Wear a respirator do not inhale fumes. IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Seek immediate medical attention. IF ON SKIN Take off immediately all contaminated clothing and wash before reuse. Wash skin with soapy water. Seek medical attention if symptoms persist. IF SWALLOWED Wash out mouth with water. Do not induce vomiting and seek immediate medical assistance. IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek immediate medical attention. Dispose of contents and packaging in accordance with all local, regional, national, and international regulations. National poison centre: 0861 555 777.



TECHNICAL DATA SHEET: CLEANERS & REMOVERS



7. PRODUCT GUARANTEE:

In the unlikely event that you are not totally satisfied - this product has a 12-month warranty. This warranty only includes replacement of the same product or a refund of the original purchase price. Product must be returned in its original packaging with proof of payment. This warranty excludes product failure caused by misuse or use of the product outside of recommended uses and instructions on the packaging.



8. PRODUCT INFORMATION:

PRODUCT NAME :		BARCODE	CODE	WEIGHT	CASE
POWASTRIP					
PRODUCT DESCRIPTION: FAST ACTING PAINT REMOVER		6009600990074	PAI500ML	500ML	6
		6009600990081	PAI1L	1LTR	6
		6009600990098	PAI5L	5LTR	2

9. PRODUCT SPECIFICATIONS -QC:

APPEARANCE :	THICK PASTE LIKE LIQUID
ODOUR :	STRONG SOLVENT
FLAMMABILITY :	N/A
DENSITY @ 20°C :	1.13
FLASH POINT :	N/A
SHELF LIFE :	MINIMUM 12 MONTHS WHEN STORED TO MANUFACTURERS RECOMMENDATIONS.

CODE & ISSUE DATE: JUNE 2021

ACE 2021

DISCLAIMER

The information contained on this document, is to the best of our knowledge, accurate. As the use of the product and site conditions are beyond our control, no further warranty is given or implied in respect of information given.