

P.DS.121
KC11 SERIES

TECHNICAL DATA SHEET

SPLOSHY



GENERAL DESCRIPTION:

Contractors Acrylic PVA is a high hiding general purpose Acrylic PVA. An interior Acrylic paint for first and finishing coats, especially ceilings and surfaces where resistance to cleaning is not required. May be used as a filler coating under medium quality acrylic PVA paints on interior walls over suitable prepared surfaces. Exterior walls except areas where water may collect.

USES:

Interior and exterior use.

FEATURES & BENEFITS:

- Low VOC
- Economical

TECHNICAL INFORMATION	
1. SPLOSHY	
PHYSICAL FORM	Non-flammable viscous liquid containing pigments and extenders. May have slight ammonia odour
COLOUR	White
FINISH	Smooth, Matt
SPREADING RATE	Approximately 6 - 8 m ² per litre per application
PRODUCT SG	1.215kg per litre
MASS SOLIDS	APP. 30%
VOL SOLIDS	APP 15%
POLYMER TYPE	Alkali-resistant acrylic copolymer latex
FILLERS	Non-toxic extenders
PIGMENTS	Weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	2 – 4 hours depending on conditions during drying
FLASH POINT	Not flammable in liquid form
PACKAGING	20L
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product. (NB: DO NOT add solvent-based thinners such as mineral turpentine)
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using water. (Some detergent may be added to water to facilitate clean up)
APPLICATION METHOD	Supplied ready-for-use. Apply using a Synthetic PVA roller or Econo PVA roller. (Do not use rollers designed for enamels)

DO NOT PAINT
IF THE TEMPERATURE IS BELOW 10 ⁰ C OR ABOVE 35 ⁰ C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

Promac Paints (Pty) Ltd.

Reg No : 1992/07244/07 VAT Nr: 4320226139

354 Derdepoort Weg, Silverton, Pretoria

P.O Box 75351, Lynwood Ridge, 0040

Tel: 012 804 7305 Fax: 012 804 6188

e-mail: info@promacpaints.co.za

www.promacpaints.co.za



P.DS.121

KC11 SERIES

HEALTH & SAFETY

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.