



## CEMENT OXIDE

### DESCRIPTION:

*Powafix Cement Oxide is a coloured organic oxide for colouring cement and other plaster materials.*

### RECOMMENDED USES:

- Decorative screeds.
- Coloured plasters.
- Coloured bricks.
- Cementitious paints.
- Coloured pond coatings.

### FEATURES & BENEFITS:

- Decorative screeds.
- Coloured plasters.
- Coloured bricks.
- Cementitious paints.

### MIXING INSTRUCTIONS:

#### CEMENTITIOUS PAINT FORMULATION:

- **Mixing Ratio:** 10kg blue/ white cement- 2kg Oxide – 5 litres Powafix Powabond and 5 ½ litres water. (Mixture must be stirred to prevent settlement)
- The above mixing ratio will coat approximately 50m<sup>2</sup>.
- Powafix Water Repellent can be used to seal and weather proof this cementitious coating.

#### DECORATIVE SCREEDS / PLASTERS:

- Use a maximum ratio of 1 part Oxide to 10 parts cement in the mix by weight.
- General plaster mix ratio is 6 parts aggregate and oxide to 1 part cement.\*
- Powafix Water Repellent is ideal for sealing dried plastered walls to protect them from rain and water damage.
- Decorative screeds mixing ratio is 4 parts aggregate and Oxide to 1 part cement.\*
- Use Powafix Powabond bonding liquid to seal and strengthen the mix. Mix Powabond at a ratio of 10 parts water to 1 part Powabond.
- Always mix the Oxide, cement and aggregate in a dry form.
- Make a small sample batch to check the final colour.
- Darker and lighter coloured aggregate and cement will affect the final colour.
- Powafix oxides are compatible with white cement and plaster of paris.

\* These are only recommended ratios, as the use of Oxides is beyond our control. Powafix cc cannot be held liable for any consequential damage arising from the use of this product.



### **SAFETY INSTRUCTIONS**

**READ INSTRUCTIONS BEFORE USE**



This product contains cement which is a potential irritant to the eyes, skin & respiratory tract.



Use protective goggles. If contact with eyes occurs, flush open eyes with plenty of water and seek immediate medical attention.



Store out of reach of children and animals. If swallowed do not induce vomiting and seek immediate medical attention.

**Poison Info. Line: 021 689 5227 / 0861 555 777**



### GALLERY:

<p>500G Packet 25 per case 6009600992047 – Black 6009600992061 – Blue 6009600992085 – Brown 6009600992108 – Green 6009600992122 – Red 6009600991385 – Yellow</p>	<p>2KG Packet 8 per case 6009600992054 – Black 6009600992078 – Blue 6009600992092 – Brown 6009600992115 – Green 6009600991378 – Red 6009600991392 – Yellow</p>

\*40KG image available on request

\*25KG image available on request

### COLOUR:

- Black (BL).
- Blue (B).
- Brown (BR).
- Green (G).
- Red (R).
- Yellow (Y).

### ASSOCIATED PRODUCTS:

- Powafix All Purpose Crack filler.
- Powafix Fill 'n Fix.
- Powafix Powabond.
- Plaster Primer.
- Powafix Sugar Soap.

### SPECIFIC DATA:

APPEARANCE:	FINE UNIFORM POWDER.
ODOUR:	NO ODOUR.

CODE & ISSUE DATE:

OXI JAN 2017

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.